PRODUCT INFORMATION

LotusPro™ Water Repellent



WolmanizedWood.com

WATER REPELLENT

Is your product shielded against these common enemies of wood?



- Moisture
 - Warping
 - Dimensional changes



- Mold
 - Surface degradation
 - · Unsightly marks or discoloration

LotusPro[™] water repellent is a barrier that contains an effective mold inhibitor, providing a protective film for your mass timber

Protect your investment and your reputation

vvith

LotusPro[™] water repellent


Patented, water-based industrial sealant technology

Lotus $\operatorname{Pro}^{\mathbb{T}}$ water repellent is made up of a specialty coating with a superhydrophobic technology coupled with an effective surface moldicide.

When applied to CLT and glulam, the coating forms a durable superhydrophobic film that both penetrates and coats the wood surface. The premium mold- and moisture-resistant coating for wood products shields the mass timber thus extending the useful life of the product.

Benefits

- Dries in 20 to 50 minutes, depending on application environment (50% faster than existing technologies)
- · Lower application rate
- UV resistance
- · Resists water absorption better than the competition
- · Resists wear and tear
- · Resists dirt pickup better than existing technologies





Allowing the beauty of your engineered wood to shine through.

LotusPro™ water repellent appears on the wood as a bright finish so the mass timber retains its natural color and overall appearance. It is compatible with oil-based and some water-based finishes.



CLT with no water repellent coating



CLT with LotusPro™ water repellent coating



CLT with LotusPro™ water repellent coating with highly compatible Minwax Polycrylic

LotusProtechnology.com

